# FUJI WIDE 1250 **0536**

## astro





## PRODUCT SPECIFICATION

#### GENERAL

FINISH: Mirror

MAIN MATERIAL: Glass - Float

**DIMENSIONS:** H: 600mm W: 1250mm D: 55mm

INSTALLATION ORIENTATION: Wall Mount - Horizontal CUT OUT HOLE: Not Applicable

RECESS DEPTH: Not Applicable FIRE RATING: Not Applicable

CABLE LENGTH:

GROSS WEIGHT:

CLASS:

CE (Class II)

IP RATING:

BATHROOM ZONE:

7000 2 3

BATHROOM ZONE: Zone 2, 3
VOLTAGE: Mains 230V

**PRODUCT F MARK:** Suitable for mounting

on flammable materials

Not Applicable

### LAMP

LIGHT SOURCE:T5MAXIMUM WATTAGE:2 x 28WMAXIMUM LAMP LENGTH:Not Applicable

LAMP INCLUDED? Yes

LUMINOUS FLUX: Lamp Dependent COLOUR TEMP: 4000 (K)

CRI: To Be Advised
R9: Lamp Dependent

MACADAM ELIPSE:

UGR: Not Applicable
BEAM ANGLE: Not Applicable
TILT ADJUSTMENT ANGLE: Not Applicable
ROTATION ADJUSTMENT ANGLE: Not Applicable
AVERAGE LIFESPAN: 12,000 (Hrs)

L70: Not Applicable

#### **ELECTRICAL**

SWITCHED: SUPPLY FREQUENCY: 50 (Hz) Yes DIMMABLE: No DRIVER/BALLAST VOLTAGE: 220-240 (V) DIMMING METHOD: Not Applicable DRIVER AVERAGE LIFESPAN: Not Applicable **DRIVER OUTPUT CURRENT:** Not Applicable EFFICACY: Lamp Dependent DRIVER OUTPUT VOLTAGE: DRIVER/BALLAST INCLUDED? Not Applicable Yes (Integral)

## ADDITIONAL INFORMATION





This product is not suitable for use with a PIR motion detector.  $\,$ 



BOX QUANTITY X1

