
IMOLA 900 LED **7507**

astro





PRODUCT SPECIFICATION

GENERAL

FINISH: Mirror CABLE LENGTH:

MAIN MATERIAL: Glass GROSS WEIGHT:

To Be Advised

DIMENSIONS:H: 900mm W: 600mm D: 48mmCLASS:CE (Class II)INSTALLATION ORIENTATION:Wall Mount - VerticalIP RATING:IP44

INSTALLATION ORIENTATION: Wall Mount - Vertical IP RATING: IP44

CUT OUT HOLE: Not Applicable BATHROOM ZONE: Zone 2, 3

RECESS DEPTH: Not Applicable VOLTAGE: Mains 230V

FIRE RATING: Not Applicable PRODUCT F MARK: Suitable for n

IRE RATING: Not Applicable PRODUCT F MARK: Suitable for mounting on flammable materials

LAMP

LIGHT SOURCE:Mid-Power LEDMACADAM ELIPSE:3-Step

MAXIMUM WATTAGE: 4 x 3.2W Mid-Power LED UGR: Not Applicable MAXIMUM LAMP LENGTH: Not Applicable **BEAM ANGLE:** Not Applicable LAMP INCLUDED? Yes (Integral) TILT ADJUSTMENT ANGLE: Not Applicable **LUMINOUS FLUX:** To Be Advised **ROTATION ADJUSTMENT ANGLE:** Not Applicable

 COLOUR TEMP:
 3000 (K)
 AVERAGE LIFESPAN:
 60,000 (Hrs)

 CRI:
 80
 L70:
 To Be Advised

ELECTRICAL

R9:

SWITCHED: Yes SUPPLY FREQUENCY: 50/60 (Hz)

DIMMABLE: No DRIVER/BALLAST VOLTAGE: 220-240 (V)

DIMMING METHOD: Not Applicable DRIVER AVERAGE LIFESPAN: 50000 (Hrs)

DRIVER OUTPUT CURRENT:350 (mA)EFFICACY:To Be AdvisedDRIVER OUTPUT VOLTAGE:Not ApplicableDRIVER/BALLAST INCLUDED?Yes (Integral)

ADDITIONAL INFORMATION



BOX QUANTITY X1

Œ

Not Applicable

12.36 (kg)



